



URGENT: Please distribute copies for the following people within your organization:

- | | | | |
|------------|-------------------------------------|---------------|-------------------------------------|
| Owner | <input checked="" type="checkbox"/> | Service Mgr | <input checked="" type="checkbox"/> |
| Sales Mgrs | <input checked="" type="checkbox"/> | Service Techs | <input checked="" type="checkbox"/> |
| Salesmen | <input checked="" type="checkbox"/> | | |

SALES Bulletin

Sales Bulletin #10

April 2006

To: All Rotary Lift Distributors and RALs

Subject: Understanding SP and SL Model Numbers

Below are tables to help you understand Rotary Lift's model numbers for SP's and SL's. Please share this chart with all appropriate members of your organization. It will be useful when shipping or receiving equipment, issuing purchase orders, paying invoices, etc.

Example: Model 1st 2nd 3rd 4th Color
 SPOA10 N 5 G 7 BL

SPO10 / SPOA10 Model Number Identification								
Model	1 st	Power	2 nd	Series	3 rd	superstructure	4 th	Height/rise
SPO12	E	3 Ø 208/220/480	2		0	Flip up adapter	0	Standard Height
SPO10	F	1 Ø / 50 Hz / 220V	3	Change to new cylinder	1	RA Adapter (2 stage arm)	1	EH1
A10i	L	3 Ø 575V	4	Change to universal overhead	2	Hunter Bolster	2	EH2
S10i	N	1 Ø / 60 Hz / 220V	5	Change to 10K models	4	Fixed Pads	5	Standard w/ 81" rise
SPOA10			6	Change inbay to version 1.6	5	No Superstructure WABU	6	EH1 w/ 81" rise
			7	Change to Formed Arms	6	Turf Attachment	7	EH2 w/ 81" rise
					8	Export RA only		
					G	3-stage arms		
					H	Honda		

SL210/SL212 Model Number Identification								
Model	1 st	Power	2 nd	Series	3 rd	superstructure	4 th	Arms / Other
SL210	E	3 Ø 208/220/480	2		0	Flip up adapter	0	Short FR - Long RR (or 3-stage) / 158" WB if DOR
SL210i	F	1 Ø / 50 Hz / 220V	3	Change to new cylinder	1	RA Adapters (2 stage arm)	1	182" WB DOR
SL212	L	3 Ø 575V	4	Change to 8.5" plungers	2	Hunter Bolster	2	Long FR - Long RR
SL212i	N	1 Ø / 60 Hz / 220V	5	Change to 10K models	3	DOR	3	Short Fr -Long RR for Workbench /or 3-stage for Workbench
			6	Change inbay to version 1.6	4	Fixed Pads	5	Long FR - Long RR for Workbench
			7	Change to new control box for inbay	5	No Superstructure WABU	9	158" WB DOR for Workbench
					G	3-stage arms	A	182" WB DOR for Workbench
					H	Honda		

Regards

Bob Ford
Product Marketing and Applications Manager

cc: Field Offices International Offices Headquarters Personnel